

floorino® heating foil

Install rule set

1. Step

The control set should be positioned where a flush-mounted box with 230 V house connection (L, N, PE) is available. Important: The controller must be located in protection zone 3. (No splash water or moisture.)

2. Step

Specify the position for the junction box. This is where all cabling for the heating foils is brought together.

3. Step

Knock a slot for a connecting pipe between the controller and the connecting pipe, and a slot from the junction box into the floor. Later, the temperature sensor should be located approx. 15 cm inside the heated floor surface.

(Chisel the subfloor sufficiently so that there is no excess height later).

4. Step

Installation of the floorino surface heating according to our installation instructions.

5. Step

Then connect all supply and return lines of the heating foils to the connection box. From the connection box, the central supply and return lines are led through the connection pipe into the controller and connected to the controller according to the "Collector line instructions".

6. Step

Position the temperature sensor in the floor and connect the cable through the conduits to the control unit according to the instructions.

7. Step

Now the heating foils can be put into operation. Turn the controller to maximum position. If everything is connected correctly, you will hear a switching and the heating foil will warm up. Check each individual foil for its function.

Then disconnect the controller from the power supply, so that you can continue working safely. Now you can start to lay the floor covering according to the instructions.

The distribution takes place via the specialized trade.

The information given in this data sheet corresponds to our knowledge and experience at the current time. However, unless expressly agreed upon, they do not constitute a warranty in the legal sense. The state of knowledge and experience is constantly evolving. Please ensure that you always use the latest edition of this data sheet. Special conditions and circumstances in individual cases cannot be taken into account in the description of product uses. Therefore, please check our products for their suitability for the final application. Status: 03/2011

**doitBau
GmbH & Co. KG**
Leipziger Str. 51
D-42109 Wuppertal
Tel. +49 202 73 95 44 30
Fax +49 202 73 95 44 39
www.floorino.com